

IMAGO

THE MATURE STAGE OF YOUR BUSINESS

ALL-IN-ONE

AL-515

AL-615A

AL-615



Imago AL-515 and AL-615 are reliable all-in-one computers dedicated for gastronomy, retail and light industry.

Equipped with a multi-touch 15" or 15.6" Full HD screen computers provide full freedom in displaying and editing data. Depending on the selected device's variant, dedicated operating system guarantee trouble-free and intuitive operation. The computers work silently due to

the fanless design with aluminium – cast housing, which ensures constant, effective cooling and enhances every workspace's style. Peripheral devices such as client's display, magnetic strip card reader, fingerprint reader or NFC reader can be integrated with.



VESA compliant



Aluminium-cast housing



Passive cooling system



Available accessories

IMAGO

ALL-IN-ONE AL-515, AL-615, AL-615A



Versions with:

dual display
magnetic card + fingerprint + NFC
VFD customer display



TECHNICAL SPECIFICATIONS

		AL-515		AL-615		AL-615A
Hardware	CPU	Intel Core N97		Intel Core N97	Intel Core i5	Intel Core RK3568
	Storage	SSD mSATA 128GB/256GB/512GB		SSD mSATA 128GB/256GB/512GB		Flash storage 64GB
	RAM	1 slot DDR III (max. 8GB)	DDR4 8GB (max. 32GB)	DDR4 8GB (max. 32GB)		4GB
Display	Size	15"		15.6" TFT LED touch screen		15.6" TFT LED touch screen
	Resolution	1024 x 768		1980 x 1080		1980 x 1080
	Brightness	350-400 cd/m ²		350-400 cd/m ²		350-400 cd/m ²
	Touch	(PCAP)		Projected Capacitive Multi-Touch Panel (PCAP)		(PCAP)
I/O	Serial	2 x COM or 2 x COM (inside the stand)	3 x COM or 2 x COM (inside the stand)	1 x COM 2 x COM (inside the stand)		1 x COM
	USB	3 x USB 2.0 1 x USB 3.0 2 x USB 2.0	4 x USB 3.0 3 x USB 2.0 (inside the stand)	4 x USB 3.0; 1 x USB 2.0 3 x USB 2.0 (inside the stand)		5 x USB 2.0
	Ethernet	1 x RJ45 (1000MB)		1 x RJ45 (1000MB)		1 x RJ45 (1000MB)
	Video port	VGA		HDMI		HDMI
	Cash drawer port	RJ11 12V	RJ11 12V or 24V	RJ12 12 V or 24V	RJ12 12V	RJ12 12V
Audio	Internal Speaker	8Ω 2W Speaker		8Ω 2W Speaker		8Ω 2W Speaker
	Line out	1 x Jack 3,5 mm		1 x Jack 3,5 mm		1 x Jack 3,5 mm
Peripherals	Magnetic strip reader (MSR)	YES (option)		YES (option)		YES (option)
	Finger print /NFC	YES (option)		YES (option)		YES (option)
	iButton	YES (option)		YES (option)		YES (option)
	Customer display	2 line VFD Display (2 x 20 characters)		2 line VFD Display (2 x 20 characters)		2 line VFD Display (2 x 20 characters)
Software	OS	Win 10 IoT Enterprise, Linux		Win 10 IoT Enterprise, Win 11, Linux		Android 11
		Win 10 IoT Enterprise, Win 11, Linux		Win 10 IoT Enterprise, Win 11, Linux		Android 11
		Win 10 IoT Enterprise, Win 11, Linux		Win 10 IoT Enterprise, Win 11, Linux		Android 11
User Environment	Operation temperature	0°C ~ ~50°C		0°C ~ ~50°C		0°C ~ ~50°C
	Storage temperature	-20°C ~ ~60°C		-20°C ~ ~60°C		-20°C ~ ~60°C
	Humidity	10% ~ ~90%		10% ~ ~90%		10% ~ ~90%
Power Supply	Voltage	DC 12V		DC 12V		DC 12V
Installation Type		Desk Stand, Wall Type		Desk Stand, Wall Type		Desk Stand, Wall Type
Dimensions	Width, height, depth (mm)	207 x 120 x 22.3		370.3 x 308 x 33		370.3 x 308 x 33
	Weight	6 kg		5.5 kg		5.5 kg



KONCEPT-L
SPÓŁKA AKCYJNA

Exclusive distributor:

phone: +48 22 512 79 00; e-mail: koncept@koncept-l.pl

KONCEPT-L.PL