

# IMAGO

THE MATURE STAGE OF YOUR BUSINESS

## ALL-IN-ONE

### AL-515

### AL-615A

### AL-615



**Imago AL-515 and AL-615 are reliable all-in-one computers dedicated for gastronomy, retail and light industry.**

Equipped with a multi-touch 15" or 15.6" Full HD screen computers provide full freedom in displaying and editing data. Depending on the selected device's variant, dedicated operating system guarantee trouble-free and intuitive operation. The computers work silently due to

the fanless design with aluminium – cast housing, which ensures constant, effective cooling and enhances every workspace's style. Peripheral devices such as client's display, magnetic strip card reader, fingerprint reader or NFC reader can be integrated with.



VESA compliant



Aluminium-cast housing



Passive cooling system



Available accessories

# IMAGO

## ALL-IN-ONE AL-515, AL-615, AL-615A



### Versions with:

- \_\_\_\_\_ dual display
- \_\_\_\_\_ magnetic card + fingerprint + NFC
- \_\_\_\_\_ VFD customer display



### TECHNICAL SPECIFICATIONS

		AL-515		AL-615			AL-615A	
Hardware	CPU	Intel Celeron J1900	Intel Core J6412	Intel Core J6412	Intel Core i3-10110U	Intel Core i5-10210U/10310U	Intel Core RK3568	
	Storage	SSD mSATA 128GB/256GB/512GB			SSD mSATA 128GB/256GB/512GB			Flash storage 64GB
	RAM	1 slot DDR III (max. 8GB)	DDR4 8GB (max. 32GB)	DDR4 8GB (max. 32GB)			4GB	
Display	Size	15"		15.6" TFT LED touch screen			15.6" TFT LED touch screen	
	Resolution	1024 x 768		1980 x 1080			1980 x 1080	
	Brightness	350-400 cd/m <sup>2</sup>		350-400 cd/m <sup>2</sup>			350-400 cd/m <sup>2</sup>	
	Touch	(PCAP)		Projected Capacitive Multi-Touch Panel (PCAP)			(PCAP)	
I/O	Serial	2 x COM or 2 x COM (inside the stand)	3 x COM or 2 x COM (inside the stand)	1 x COM 2 x COM (inside the stand)			1 x COM	
	USB	3 x USB 2.0 1 x USB 3.0 2 x USB 2.0	4 x USB 3.0 3 x USB 2.0 (inside the stand)	4 x USB 3.0; 1 x USB 2.0 3 x USB 2.0 (inside the stand)			5 x USB 2.0	
	Ethernet	1 x RJ45 (1000MB)		1 x RJ45 (1000MB)			1 x RJ45 (1000MB)	
	Video port	VGA		HDMI			HDMI	
	Cash drawer port	RJ11 12V	RJ11 12V or 24V	RJ12 12 V or 24V	RJ12 12V		RJ12 12V	
Audio	Internal Speaker	8Ω 2W Speaker		8Ω 2W Speaker			8Ω 2W Speaker	
	Line out	1 x Jack 3,5 mm		1 x Jack 3,5 mm			1 x Jack 3,5 mm	
Peripherals	Magnetic strip reader (MSR)	YES (option)		YES (option)			YES (option)	
	Finger print /NFC	YES (option)		YES (option)			YES (option)	
	iButton	YES (option)		YES (option)			YES (option)	
	Customer display	2 line VFD Display (2 x 20 characters) 9.7" (non touch) 9.7" (touch)		2 line VFD Display (2 x 20 characters) 11.6" or 15.6" (non touch) 11.6" or 15.6" (touch)			2 line VFD Display (2 x 20 characters) 11.6" or 15.6" (non touch) 11.6" or 15.6" (touch)	
Software	OS	Win 10 IoT Enterprise, Linux	Win 10 IoT Enterprise, Win 11, Linux	Win 10 IoT Enterprise, Win 11, Linux			Android 11	
User Environment	Operation temperature	0°C – ~50°C		0°C – ~50°C			0°C – ~50°C	
	Storage temperature	-20°C – ~60°C		-20°C – ~60°C			-20°C – ~60°C	
	Humidity	10% – ~90%		10% – ~90%			10% – ~90%	
Power Supply	Voltage	DC 12V		DC 12V			DC 12V	
Installation Type		Desk Stand, Wall Type		Desk Stand, Wall Type			Desk Stand, Wall Type	
Dimensions	Width, height, depth (mm)	207 x 120 x 22.3		370.3 x 308 x 33			370.3 x 308 x 33	
	Weight	6 kg		5.5 kg			5.5 kg	



**KONCEPT-L**  
SPÓŁKA AKCYJNA

Exclusive distributor:

phone: +48 22 512 79 00; e-mail: [koncept@koncept-l.pl](mailto:koncept@koncept-l.pl)

**KONCEPT-L.PL**